

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0751-CPR.2-008.2-01

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Factory made mineral wool (MW) products for thermal insulation of building
equipment and industrial installations**
(details cf. annex)

Placed on the market under the name or trade mark of

Deutsche Rockwool GmbH & Co. KG

Rockwool Str. 37-41
45966 Gladbeck
Germany

and produced in the manufacturing plant

Rockwool B.V.

Industrieweg 15
6040 KD Roermond
Netherlands

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14303:2009+A1:2013

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 09.09.2016 and will remain valid (but no longer than 01.08.2023) as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body

Gräfelfing, 01.08.2022



Certification Body

Ralph Alberti
Ralph Alberti

A publication of extracts or a referring to the Certificate of Constancy of Performance and its annex requires the prior written approval of FIW München. Certification body accredited by DAkkS according to EN/ISO IEC 17065:2013 according to the certification annex D-ZE-14116-01-00.

Factory:

Rockwool B.V., Industrieweg 15, 6040 KD Roermond, Netherlands

Construction product(s):

Factory made mineral wool (MW) products for thermal insulation of building equipment and industrial installations according to EN 14303:2009+A1:2013

Intended use:

Thermal insulation products for building equipment and industrial installations

Level(s) or class(es) reaction to fire:

for uses subject to regulations on reaction to fire A1/A2 and A1L/A2L. Products for which a clearly identifiable stage in the production process results in an improvement in the reaction to fire classification by limiting of organic material.

Product					Reaction to fire EN 13501-1		
No.	Form	Name	Description	Classification	Range	Fire Group	Classification report
1	Slab	Rockwool Aluboard (Rockwool Flexiboard ALU)	Non-combustible mineral wool slab covered with reinforced aluminum foil	A1	Max. organic content: 2,8 kg/m ³ Thickness: 25 mm - 200 mm Density: 39 kg/m ³ -145 kg/m ³ Production line: ROE3	1	230008256-4
2	Pipe section	Rockwool 800	Non-combustible mineral wool concentrically wound pipe section faced with reinforced aluminum foil	A2L-s1, d0	Do ≤ 300 mm Max. organic content: 7,2 kg/m ³ Density: 90 kg/m ³ to 180 kg/m ³ Thickness: ≥ 20 mm and ≤ 50 mm Production line: ROE2, PU1, PU2	13	230008366-4
3	Pipe section	Rockwool 800	Non-combustible mineral wool concentrically wound pipe section faced with reinforced aluminum foil	A2-s1,d0	Do > 300 mm Max. organic content: 2,22 kg/m ³ Density: 90 kg/m ³ to 119 kg/m ³ Thickness: ≥ 20 mm and ≤ 80 mm Production line: ROE2, PU1	14	230008366-4
4	Pipe section	Rockwool 800	Non-combustible mineral wool concentrically wound pipe section faced with reinforced aluminum foil	A2-s1,d0	Do > 300mm Max. organic content: 5,9 kg/m ³ Density: ≤152 kg/m ³ Thickness: ≤100mm Production line: ROE2, PU2	21	YA-2280-2E-RA-003

Product			Reaction to fire EN 13501-1				
No.	Form	Name	Description	Classification	Range	Fire Group	Classification report
5	Pipe section	Rockwool 835	Non-combustible mineral wool concentrically wound pipe section	A1L	Max. organic content: 3,22 kg/m ³ Production line: ROE2, PU1, PU2	5	230007544-3
6	Pipe section	Tecit PS Cold	Non-combustible mineral wool concentrically wound pipe section faced with reinforced aluminum foil	A2L-s1, d0	Do ≤ 300 mm Max. organic content: 3,1 kg/m ³ Density: 100 kg/m ³ ± 15 % Thickness: ≥ 20 mm Production line: ROE2, PU1, PU2	4	230010470-3
7	Pipe section	Tecit PS Cold	Non-combustible mineral wool concentrically wound pipe section faced with reinforced aluminum foil	A2-s1,d0	Do > 300 mm Max. organic content: 2,22 kg/m ³ Density: 100 kg/m ³ ± 15 % Thickness: ≥ 20 mm Production line: ROE2, PU1, PU2	6	230010471-2
8	Pipe section	Tecit PS Cold TB	Non-combustible mineral wool concentrically wound pipe section without longitudinal cut and faced with reinforced aluminum foil	A2L-s1, d0	Do ≤ 300 mm Max. organic content: 3,1 kg/m ³ Density: 100 kg/m ³ ± 15 % Thickness: ≥ 20 mm Production line: ROE2, PU2	94	230010470-3
9	Pipe section	Tecit PS Cold TB	Non-combustible mineral wool concentrically wound pipe section without longitudinal cut and faced with reinforced aluminum foil	A2-s1,d0	Do > 300 mm Max. organic content: 2,22 kg/m ³ Density: 100 kg/m ³ ± 15 % Thickness: ≥ 20 mm Production line: ROE2, PU2	96	230010471-2

Detail information about the insulation products are given in the classification reports

Gräfelfing 01.08.2022

